



8271

STYLEKIT 5 WIRE - SINGLE USER



Style Kit 5 is the ideal door entry phone kit which uses 5 wires and is available from single-family to four-family versions. Style Kit 5 has an original and innovative design characterised by its unmistakable and exclusive blue LEDs, by large name labels and by high sound quality. Options to add an additional handsets or sounders.



8271

STYLEKIT 5 WIRE - SINGLE USER

KIT PRODUCTS



3554 FLUSH BOX FOR STYLEKIT RANGE

Flush-mounting box. Dimensions: 95,5x176,5x35mm

MAIN FEATURES

Height (mm)	176.5
Width (mm)	95.5
Depth (mm)	35

MOUNTING/INSTALLATION

Flush-mounted	Si
---------------	----

AUDIO/VIDEO FEATURES

Audio system	Yes
Audio/video system	Yes



8271

STYLEKIT 5 WIRE - SINGLE USER



3551 5 WIRE SURFACE PANEL FOR STYLEKIT - 1 BUTTON

Surface mount 1 button door entry panel for use with the 8271 audio kit. Features include a large illuminated name window with LED, complete with speaker unit and volume adjustment. Dimensions of external unit:95x176x25mm



8271

STYLEKIT 5 WIRE - SINGLE USER



2602 BASIC DOOR ENTRY PHONE FOR STYLEKIT 5

Door-entry phone with electronic call function, conversation button on base, call volume control and privacy function, key button and supplementary button for additional services with independent common. On this model it is not possible to add extra buttons or LEDs. Dimensions: 95x215x58 mm.

GENERAL DATA

Height (mm)	215
Width (mm)	95
Depth (mm)	58

SETTINGS

Loudspeaker volume control	Yes
Microphone volume control	Yes
Ringtone volume control	Yes

MAIN FEATURES

Audio system	Yes
Wall-mounted	Si
Desk base-mounted	Si
Total buttons (n°)	2

FUNCTIONS

Privacy function	Yes
Electronic bell	Yes
Privacy conversation function	Yes
Key button function	Yes

COMPATIBILITY

Traditional system	Yes
--------------------	-----



8271

STYLEKIT 5 WIRE - SINGLE USER

TECHNICAL CHARACTERISTICS

IP protection rating	IP30
Operating temperature (°C)	-5 ÷ 40
Weight (g)	400
Clamps	S 2 3 4 C1 P1 C2 P2



8271

STYLEKIT 5 WIRE - SINGLE USER



1200 TRANSFORMER 10VA 0-230V/0-12V

Power Supply. 230V input, 12V AC / 900 mA output for continuous use. Dimensions: 53x95x65 mm (3 DIN modules).

MAIN FEATURES

Supply voltage	230
Input connector	Terminal block
Applicable to DIN rail	Yes
Number of DIN modules (n°)	3
Max. current delivered (A)	0.9

GENERAL DATA

Height (mm)	95
Width (mm)	53
Depth (mm)	65
Type of finish	Plastic
Operating temperature (°C)	-5 ÷ 40

COMPATIBILITY

Simplebus 2 audio/video system	Yes
Building Kit audio/video system	Yes
Simplebus 2 audio system	Yes
Simplebus 1 audio system	Yes
Vip system	Yes
Kit audio/video system	Yes
Traditional system	Yes
Simplified system	Yes

ELECTRICAL SPECIFICATIONS

Maximum power delivered (W)	15
-----------------------------	----



8271

STYLEKIT 5 WIRE - SINGLE USER

ACCESSORIES



4889

RAINSHIELD FOR FLUSH MOUNTED IDEALKIT

Rain shield for Ideal flush-mounted panel Dimensions:
115x195x52mm



4887

RAINSHIELD FOR SURFACE MOUNTED IDEALKIT

Housing with rain shield for Ideal wall-mounted panel. Dimensions:
119x196x76 mm



3550

5 WIRE FLUSH PANEL FOR STYLEKIT - 1 BUTTON

Flush mount 1 button door entry panel for use with the 8271 audio kit. Features include a large illuminated name window with LED, complete with speaker unit and volume adjustment. Dimensions of flush-mounted box:95.5x176.5x35mm



2642W/28 WHITE DESK BASE FOR STYLE 28 WIRE

White desk conversion kit for Style series handsets. Complete with 1.5 mt of white cable and connection fitted with 28 connection terminals. Dimensions 84X189X32 mm.



2642W/16 WHITE DESK BASE FOR STYLE 16 WIRE

White desk conversion kit for Style series handsets. Complete with 1.5 mt of white cable and connection fitted with 16 connection terminals. Dimensions 84X189X32 mm.



1627

LED FOR STYLE ELEGANCE H/SET

Blue LED to be inserted in the base of the Style Elegance handsets. 12-24V AC-DC operation.



8271

STYLEKIT 5 WIRE - SINGLE USER

ACCESSORIES



1626

STYLE INTERCOM ADDITIONAL PUSH BUTTON


Pushbutton to be inserted in the base of the Style Elegance handsets.



1229

EXTENSION SOUNDER

Additional sounder for call repetition can be controlled directly from terminals S- and S+ of the brackets and/or from the telephones. Surface mounted. Dimensions: 110X75X29 mm.



1122/A

RELAY 12/24 AC OR DC

12/24v AC or DC Single Pole relay. Dimensions 66x85x35mm